NSN 5310-01-132-5623

Spring Tension Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-132-5623

| Hole Diameter: |
|-------------------------------------------------------------------------------------------------------------------------------------------|
| Between 0.683 inches and 0.694 inches |
| Outside Diameter: |
| Between 1.159 inches and 1.171 inches |
| Overall Height: |
| Between 0.039 inches and 0.050 inches |
| Material Thickness: |
| Between 0.015 inches and 0.019 inches |
| Hardness Rating: |
| 52.0 rockwell c |
| Material: |
| Steel comp 6150 or steel comp 301 or steel comp 302 |
| Material Specification: |
| Aisi assn standard 1st material response or qq-s-766 federal specification 2nd material response or mil-s-5059 military specification 2nd |
| material response or qq-s-766 federal specification 3rd material response or mil-s-5059 military specification 3rd material response |
| Surface Treatment: |
| Nickel or passivate |
| Surface Treatment Specification: |
| Mil-c-26074, cl 2 military specification 1st treatment response or qq-p-35 federal specification 2nd treatment response |
| Style Designator: |
| Spring tension |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A022b0 |
| Mil-std (military Standard): |
| Mil-s-5059 spec. |
| |