

View Online at <https://aerobasegroup.com/nsn/5310-01-132-8554>

Hole Diameter:

Between 0.601 inches and 0.616 inches

Outside Diameter:

Between 0.797 inches and 0.827 inches

Internal Prebent Key Length:

Between 0.062 inches and 0.093 inches

External Prebent Key Width:

Between 0.110 inches and 0.120 inches

Internal Prebent Key Width:

Between 0.110 inches and 0.120 inches

Overall Distance Including Keys:

Between 1.0935 inches and 1.1560 inches

External Key Quantity:

11

Material Thickness:

Between 0.038 inches and 0.046 inches

Criticality Code Justification:

Zzzy

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 303pb or steel comp 304 or steel comp 304l or steel comp 304h

Material Specification:

Aisi, cond a assn standard all material responses

Special Test Features:

Special quality control testing

Style Designator:

Key

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions and certified free from mercury contamination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A022b0