## NSN 5310-01-134-5785

Assembled Washer Self-locking Nut - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5310-01-134-5785                                    |
|--|
| Thread Class:  |
| 3b   |
| Thread Direction:  |
| Right-hand   |
| Locking Feature:   |
| Prevailing torque all metal design   |
| Washer Outside Diameter:   |
| 0.395 inches   |
| Counterbore Diameter:  |
| 0.211 inches nut and 0.221 inches nut  |
| Lubrication:   |
| Dry film lubricant   |
| Overall Height:  |
| 0.243 inches   |
| Nut Counterbore Depth:   |
| 0.065 inches nut   |
| Width Across Flats:  |
| Between 0.243 inches and 0.251 inches  |
| Tempurature Rating:  |
| 450.0 degrees fahrenheit   |
| Thread Series:   |
| Unjf   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Thread Size:   |
| 0.190 inches   |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams5732 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A021a0   |