## NSN 5310-01-135-8673

Round Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-135-8673

| Thread Class:  |
|--|
| 3b   |
| Thread Direction:  |
| Right-hand   |
| Small End Diameter:  |
| 3.656 inches   |
| Nut Style:   |
| Round  |
| Nut Thickness:   |
| 0.600 inches   |
| Undercut Thickness:  |
| 0.060 inches   |
| Drive Point Quantity:  |
| 8  |
| Hole Type And Quantity:  |
| 16 tapped  |
| Thread Series:   |
| Un   |
| Thready Qty Per Inch (tpi):  |
| 16   |
| Hardness Rating:   |
| Between 26.0 rockwell c and 33.0 rockwell c                        |
| Thread Size:   |
| 3.125 inches   |
| Hole Thready Qty Per Inch (tpi):                                   |
| 28   |
| Hole Configuration Style:  |
| Configuration j  |
| Hole Thread Diameter:  |
| 0.250 inches   |
| Material:  |
| Steel comp 4340  |
| Material Specification:  |
| Mil-s-5000, cond c military specification single material response |
| Surface Treatment:   |
| Phosphate  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |

## NSN 5310-01-135-8673

Round Self-locking Nut - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.

