NSN 5310-01-136-5753

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-136-5753 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.195 inches nut and 0.200 inches nut Lubrication: Dry film lubricant **Overall Height:** 0.383 inches **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** Between 1.360 inches and 1.390 inches Nut Height: 0.373 inches **Plate Thickness:** Between 0.023 inches and 0.027 inches Plate Width: 0.865 inches **Nut Counterbore Depth:** 0.178 inches nut and 0.188 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.557 inches and 0.567 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 1.123 inches and 1.127 inches **Thread Series:** Unif Thready Qty Per Inch (tpi):

Features Provided: Floating nut 28 **Thread Size:** 0.250 inches

NSN 5310-01-136-5753

Plate Self-locking Nut - Page 2 of 2

Fiig: A021a0



Material:
Steel comp 601 channel
Material Specification:
Ams 5732 assn standard single material response nut
Surface Treatment:
Passivate except threads
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response except threads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No