

View Online at <https://aerobasegroup.com/nsn/5310-01-137-7062>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Lubrication:

Dry film lubricant

Nut Style:

Hexagon

Nut Height:

Between 0.473 inches and 0.656 inches

Width Across Flats:

Between 0.861 inches and 0.877 inches

Tempurature Rating:

250.0 degrees fahrenheit

Thread Series:

Unf

Thready Qty Per Inch (tpi):

18

Thread Size:

0.562 inches

Bearing Surface Type:

Chamfered or washer faced

Material:

Steel comp 1013 nut or steel comp 1015 nut or steel comp 1016 nut or steel comp 1017 nut or steel comp 1018 nut or steel comp 1019 nut or steel comp 1020 nut or steel comp 1021 nut or steel comp 1022 nut or steel comp 1023 nut or steel comp 1524 nut or steel comp 1025 nut or steel comp 1026 nut or steel comp 1527 nut or steel comp 1029 nut or steel comp 1030 nut or steel comp 1033 nut or steel comp 1034 nut or steel comp 1035 nut or steel comp 1536 nut or steel comp 1037 nut or steel comp 1038 nut or steel comp 1039 nut or steel comp 1040 nut or steel comp 1541 nut

Material Specification:

Sae assn standard all material responses nut

Surface Treatment:

Phosphate zinc except insert

Surface Treatment Specification:

Mil-p-16232, ty z, cl 2 military specification single treatment response except insert

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):