

View Online at <https://aerobasegroup.com/nsn/5310-01-138-4717>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design or prevailing torque with nonmetallic insert

**Pilot Diameter:**

Between 0.321 inches and 0.325 inches

**Pilot Length:**

Between 0.110 inches and 0.140 inches

**Lubrication:**

Dry film lubricant

**Nut Style:**

Spline

**Nut Height:**

Between 0.267 inches and 0.327 inches

**Width Across Flats:**

Between 0.423 inches and 0.453 inches

**Tempurature Rating:**

250.0 degrees fahrenheit

**Thread Series:**

Unf

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Material:**

Steel comp 1013 nut or steel comp 1015 nut or steel comp 1016 nut or steel comp 1017 nut or steel comp 1018 nut or steel comp 1019 nut or steel comp 1020 nut or steel comp 1021 nut or steel comp 1022 nut or steel comp 1023 nut or steel comp 1524 nut or steel comp 1025 nut or steel comp 1026 nut or steel comp 1527 nut or steel comp 1029 nut or steel comp 1030 nut or steel comp 1033 nut or steel comp 1034 nut or steel comp 1035 nut or steel comp 1536 nut or steel comp 1037 nut or steel comp 1038 nut or steel comp 1039 nut or steel comp 1040 nut or steel comp 1541 nut

**Surface Treatment:**

Cadmium nut

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0