NSN 5310-01-143-5050

Key Washer - Page 1 of 2

No



| view Online at https://aerobasegroup.com/nsn/5310-01-145-5050 |
|--|
| Hole Diameter: |
| Between 2.280 inches and 2.300 inches |
| Outside Diameter: |
| Between 2.837 inches and 2.857 inches |
| External Straight Key Width: |
| Between 0.150 inches and 0.170 inches |
| Internal Straight Key Width: |
| Between 0.290 inches and 0.300 inches |
| Distance From Centerline To Top Of Internal Key: |
| Between 0.935 inches and 0.955 inches |
| Overall Distance Including Keys: |
| Between 3.037 inches and 3.057 inches |
| External Key Quantity: |
| 4 |
| Internal Key Quantity: |
| 2 |
| Material Thickness: |
| Between 0.046 inches and 0.054 inches |
| Hardness Rating: |
| Between 32.0 rockwell c and 36.0 rockwell c |
| Surface Finish: |
| 63.0 microinches top |
| Product Name: |
| Navy special project |
| Special Features: |
| Internal keys 180.0 degrees apart offset 17 degrees 36 min 31 sec from center line of external keys |
| Material: |
| Steel comp 4130 or steel comp 4340 |
| Material Specification: |
| Mil-s-18729 military specification 1st material response or ams 6415 assn standard 2nd material response |
| Surface Treatment: |
| Phosphate |
| Surface Treatment Specification: |
| Dod-p-16232, ty z, cl 4 military specification single treatment response |
| Style Designator: |
| Key |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5310-01-143-5050

Key Washer - Page 2 of 2



Fiig:

A022b0

Mil-std (military Standard):

Mil-s-18729 spec.