NSN 5310-01-144-0998



Plate Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-144-0998 **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 4.4 millimeters nut Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 2.5 millimeters and 2.7 millimeters **Nut Style:** Plate **Nut Length:** 26.4 millimeters **Nut Height:** Between 5.0 millimeters and 5.8 millimeters **Plate Thickness:** 0.6 millimeters Plate Width: 10.6 millimeters **Nut Counterbore Depth:** 2.2 millimeters nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** 8.5 millimeters Center To Center Distance Between Mounting Holes Along Length: 8.0 millimeters **Tempurature Rating:** 235.0 degrees celsius **Thread Series:** Mį **Features Provided:** Floating nut **Thread Size:** 4.0 millimeters **Thread Pitch In Millimeters:**

0.70

Thread Tolerance Class:

4h6h internal

NSN 5310-01-144-0998

Plate Self-locking Nut - Page 2 of 2

A021a0



Material:
Steel
Surface Treatment:
Cadmium and chromate or cadmium and phosphate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification 1st treatment response or qq-p-416, type 3, cl 2 federal specification 2nd treatment response
Specification Data:
30205-nas0073 professional/industrial association standard
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg: