

View Online at <https://aerobasegroup.com/nsn/5310-01-145-0813>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.781 inches nut and 0.791 inches nut

Lubrication:

Dry film lubricant

Nut Style:

Non-floating self-locking barrel

Nut Diameter:

Between 1.2375 inches and 1.2405 inches

Nut Length:

Between 1.209 inches and 1.229 inches

Barrel Height:

Between 0.729 inches and 0.749 inches

Nut Height:

0.982 inches

Nut Counterbore Depth:

0.190 inches nut and 0.210 inches nut

Temperature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Thready Qty Per Inch (tpi):

16

Thread Size:

0.750 inches

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-s-5000 spec.