

View Online at <https://aerobasegroup.com/nsn/5310-01-147-4910>

Thread Pitch Diameters:

+6.2028/+6.2119 inches

Thread Direction:

Right-hand

Drive Point Depth:

0.281 inches

Nut Style:

Round

Nut Diameter:

Between 8.047 inches and 8.067 inches

Nut Thickness:

Between 1.016 inches and 1.041 inches

Drive Point Width:

Between 0.610 inches and 0.635 inches

Drive Point Quantity:

4

Thread Series:

Uns

Thready Qty Per Inch (tpi):

8

Hardness Rating:

Between 66.0 rockwell b and 92.0 rockwell b

Thread Size:

6.284 inches

Countersink Angle:

60.0 degrees both ends and 90.0 degrees both ends

Material:

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1031 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1212 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1213 or steel comp 1215

Material Specification:

66 federal standard all material responses

Surface Treatment:

Zinc and chromate

Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification single treatment response

Specification Or Standard:

1 type and 2 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-n-21337 spec.