

View Online at <https://aerobasegroup.com/nsn/5310-01-148-9780>

Hole Diameter:

Between 6.389 inches and 6.424 inches

Outside Diameter:

Between 7.438 inches and 7.498 inches

Internal Prebent Key Length:

Between 0.312 inches and 0.374 inches

External Prebent Key Width:

Between 0.480 inches and 0.520 inches

Internal Prebent Key Width:

Between 0.500 inches and 0.590 inches

Overall Distance Including Keys:

8.438 inches

External Key Quantity:

19

Material Thickness:

Between 0.148 inches and 0.164 inches

Hardness Rating:

Between 50.0 brinell and 81.0 brinell

Heat Treatment:

Annealed

Material:

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1035

Material Specification:

66 federal standard all material responses

Surface Treatment:

Zinc and chromate or cadmium and chromate

Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification 1st treatment response or qq-p-416, type 2, cl 3 federal specification 2nd treatment response

Style Designator:

Key

Specification Or Standard:

1 type and 1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A022b0