

View Online at <https://aerobasegroup.com/nsn/5310-01-155-4373>

**Thread Pitch Diameters:**

+1.3399/+1.3439 inches

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Drive Point Depth:**

0.094 inches

**Nut Style:**

Round

**Nut Diameter:**

2.057 inches

**Nut Thickness:**

0.438 inches

**Drive Point Width:**

0.188 inches

**Drive Point Quantity:**

4

**Temperature Rating:**

Between -60.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Thread Series:**

Uns

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

Between 66.0 rockwell b and 92.0 rockwell b

**Thread Size:**

1.376 inches

**Countersink Angle:**

90.0 degrees both ends and 120.0 degrees both ends

**Material:**

Steel comp 1015 nut or steel comp 1016 nut or steel comp 1017 nut or steel comp 1018 nut or steel comp 1019 nut or steel comp 1020 nut or steel comp 1021 nut or steel comp 1022 nut or steel comp 1023 nut or steel comp 1025 nut or steel comp 1026 nut or steel comp 1029 nut or steel comp 1030 nut or steel comp 1031 nut or steel comp 1033 nut or steel comp 1034 nut or steel comp 1035 nut or steel comp 1116 nut or steel comp 1117 nut or steel comp 1118 nut or steel comp 1212 nut or steel comp 1213 nut or steel comp 1215 nut

**Surface Treatment:**

Cadmium nut and chromate nut or passivate nut

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification 1st treatment response nut or qq-p-35 federal specification 2nd treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0