

View Online at <https://aerobasegroup.com/nsn/5310-01-156-5450>

Mounting Hole Diameter:

Between 0.102 inches and 0.108 inches

Nut Style:

Plate nut spacer

Nut Length:

Between 0.807 inches and 0.822 inches

Thru-hole Diameter:

Between 0.270 inches and 0.280 inches

Plate Thickness:

Between 0.026 inches and 0.038 inches

Plate Width:

Between 0.399 inches and 0.414 inches

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.278 inches and 0.284 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.217 inches and 0.221 inches

Material:

Steel comp 1010 or steel comp 1020 or steel comp 1025 or steel comp 4130

Material Specification:

Mil-s-7952 military specification 2nd material response or mil-s-7952 military specification 3rd material response or mil-s-18729, cond n military specification 4th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Specification Data:

80205-nas1195 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-7952 spec.