

310-01-163-8250

| View Online at https://aerobasegroup.com/nsn/53 |
|---|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Counterbore Diameter: |
| 0.154 inches nut |
| Lubrication: |
| Dry film lubricant |
| Overall Length: |
| 72.000 inches |
| Overall Width: |
| 0.552 inches |
| Nut Style: |
| A20 gang channel, self locking |
| Removable Nut Manufacturer Code: |
| 76301 |
| Channel Style: |
| Straight type |
| Assemblyheight: |
| 0.605 inches |
| Channel Height: |
| 0.298 inches |
| Nut Spacing: |
| Between 0.865 inches and 0.885 inches |
| Nut Counterbore Depth: |
| 0.375 inches nut |
| Removable Nut Manufacturer Part Number: |
| St3m445a4m6 |
| Tempurature Rating: |
| 350.0 degrees fahrenheit |
| Nut Quantity: |
| 82 |
| Thread Series: |
| Unjf |
| Features Provided: |
| Floating nut |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches |
| |

NSN 5310-01-163-8250

Gang Channel Self-locking Nut Assembly - Page 2 of 2



Material:

Steel nut

Material Specification:

Qq-a-250/13, t6 federal specification single material response channel

Surface Treatment:

Cadmium and chromate nut

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No Fiig: A021a0

Mil-std (military Standard):

Mil-a-8625 spec.