

View Online at <https://aerobasegroup.com/nsn/5310-01-168-1767>

Thread Class:

3b

Thread Direction:

Right-hand

Nut Style:

Hexagon

Nut Height:

0.112 inches

Drilled Hole Diameter:

Between 0.034 inches and 0.039 inches

Hole Type And Quantity:

3 drilled

Width Across Flats:

0.376 inches

Thread Series:

Unjc

Thready Qty Per Inch (tpi):

32

Hardness Rating:

Between 34.0 rockwell c and 38.0 rockwell c

Thread Size:

0.164 inches

Hole Configuration Style:

Configuration b

Countersink Angle:

110.0 degrees both ends

Bearing Surface Type:

Chamfered or washer faced

Bearing Surface Finish:

125.0 microinches

Material:

Steel comp 4130 or steel comp 4340

Material Specification:

Mil-s-6758, cond d-1 or d-4 or f-4 military specification 1st material response or mil-s-5000, cond c-1 or c-4 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-35, type 2, cl 2 federal specification single treatment response

Specification Data:

80205-nas1423 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-6758 spec.