## NSN 5310-01-168-9032

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-168-9032 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.194 inches nut **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 1.051 inches **Nut Height:** 0.437 inches **Plate Thickness:** 0.032 inches Plate Width: 0.416 inches **Nut Counterbore Depth:** 0.250 inches nut and 0.265 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.310 inches and 0.314 inches **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches Material:

**Material Specification:** 

Iron alloy 660

Ams 5732 assn standard single material response or ams 5731 assn standard single material response or ams 5525 assn standard single material response

## **NSN 5310-01-168-9032**Plate Self-locking Nut - Page 2 of 2



Precious Material And Location:
Threads silver
Precious Material:
Silver
Surface Treatment:
Silver threads
Surface Treatment Specification:
Ams 2410 assn standard single treatment response threads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A021a0