

View Online at https://aerobasegroup.com/nsn/5310-01-169-6775

| Thread Class: |
|---|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Counterbore Diameter: |
| 0.317 inches nut |
| Lubrication: |
| Dry film lubricant |
| Overall Length: |
| 71.775 inches |
| Overall Width: |
| 0.652 inches |
| Nut Style: |
| A20 gang channel, self locking |
| Removable Nut Manufacturer Code: |
| 76301 |
| Channel Style: |
| Straight type |
| Assemblyheight: |
| 0.400 inches |
| Channel Height: |
| 0.344 inches |
| Nut Spacing: |
| 1.625 inches |
| Nut Counterbore Depth: |
| 0.125 inches nut |
| Removable Nut Manufacturer Part Number: |
| St3m445c5m2 |
| Nut Quantity: |
| 44 |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.312 inches |
| Material: |
| Iron alloy 660 nut |
| Material Specification: |

Qq-a-250/13, t6 federal specification single material response channel



Surface Treatment:

Nickel or copper nut

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response channel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.