

View Online at <https://aerobasegroup.com/nsn/5310-01-172-0030>

Hole Diameter:

Between 0.880 inches and 0.896 inches

Outside Diameter:

1.640 inches

External Straight Key Length:

0.240 inches

External Straight Key Width:

0.250 inches

Material Thickness:

0.060 inches

Wire Hole Diameter:

Between 0.062 inches and 0.072 inches

Special Features:

Two key lugs are raised 0.061 in. Min, 0.071 in. Maximum above washer face; spaced diametrically on radial centerline bisecting external key; both keys are 0.137 in. Wide min, 0.147 in. Wide max; outer edges 1.150 in. Nom apart; inner edges 0.782 in. Min, 0.802 in. Maximum apart; tensile strength 180000 to 200000 psi

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Cadmium

Special Test Features:

Penetrant insp. Ps21202 class a, fscm 76301

Surface Treatment Specification:

Ps 13145, class 1, type 2, fscm 76301 mfr ref single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0

Mil-std (military Standard):

Mil-s-5000 spec.