

View Online at <https://aerobasegroup.com/nsn/5310-01-172-0030>

**Hole Diameter:**

Between 0.880 inches and 0.896 inches

**Outside Diameter:**

1.640 inches

**External Straight Key Length:**

0.240 inches

**External Straight Key Width:**

0.250 inches

**Material Thickness:**

0.060 inches

**Wire Hole Diameter:**

Between 0.062 inches and 0.072 inches

**Special Features:**

Two key lugs are raised 0.061 in. Min, 0.071 in. Maximum above washer face; spaced diametrically on radial centerline bisecting external key; both keys are 0.137 in. Wide min, 0.147 in. Wide max; outer edges 1.150 in. Nom apart; inner edges 0.782 in. Min, 0.802 in. Maximum apart; tensile strength 180000 to 200000 psi

**Material:**

Steel comp e4340

**Material Specification:**

Mil-s-5000 military specification single material response

**Surface Treatment:**

Cadmium

**Special Test Features:**

Penetrant insp. Ps21202 class a, fscm 76301

**Surface Treatment Specification:**

Ps 13145, class 1, type 2, fscm 76301 mfr ref single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0

**Mil-std (military Standard):**

Mil-s-5000 spec.