

View Online at <https://aerobasegroup.com/nsn/5310-01-175-0617>

Thread Class:

2b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Nut Style:

Hexagon

Nut Height:

Between 0.720 inches and 0.750 inches

End Application:

W/s: aircraft, t-39; truck, ambulance, 2-litter, soft top, 1 1/4 ton hmwv; truck, vehicle system, 1 1/4-ton (hmwv); truck, utility, cargo troop carrier, 5/4-ton w/e (m998)

Width Across Flats:

Between 1.545 inches and 1.575 inches

Thread Series:

Unef

Thread Qty Per Inch (tpi):

20

Thread Size:

0.875 inches

Bearing Surface Type:

Chamfered

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Phosphate

Surface Treatment Specification:

Gm 4435-m, code a, fscm 34623 mfr ref single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0