## NSN 5310-01-175-1027

Plate Self-locking Nut - Page 1 of 2

**Thread Class:** 

3b

View Online at https://aerobasegroup.com/nsn/5310-01-175-1027



**Thread Direction: Right-hand Distance From Centerline To Flat:** Between 0.236 inches and 0.241 inches Locking Feature: Prevailing torque all metal design **Counterbore Diameter:** 0.254 inches nut Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches Nut Style: Plate Nut Length: 0.617 inches Nut Height: 0.273 inches **Plate Thickness:** 0.036 inches Plate Width: 0.498 inches Nut Counterbore Depth: 0.062 inches nut and 0.077 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.276 inches and 0.286 inches Center To Center Distance Between Mounting Holes Along Width: Between 0.217 inches and 0.221 inches **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches

## NSN 5310-01-175-1027

Plate Self-locking Nut - Page 2 of 2



Material:

Iron alloy 660

## Material Specification:

Ams 5525 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate shell

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A021a0