

View Online at <https://aerobasegroup.com/nsn/5310-01-184-3786>

**Hole Diameter:**

Between 0.785 inches and 0.800 inches

**Outside Diameter:**

1.200 inches

**Tapered Key Minor Width:**

0.120 inches

**Overall Distance Including Keys:**

Between 1.470 inches and 1.570 inches

**Material Thickness:**

0.063 inches

**Wire Hole Diameter:**

Between 0.070 inches and 0.075 inches

**Special Features:**

Distance from wire hole center to end of tapered key 0.060 in.; distance from wire hole center to top of tapered prebent key 0.120 in.; tapered key prebent 30 degrees min, 40 degrees max; hole width across flats 0.655 in. Min, 0.670 in. Max; distance from centerline to flattened bottom of washer 0.485 in. Min, 0.515 in. Max; distance from bottom of washer to inside of prebent key 1.160 in.

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/4, t4 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, type 2, cl 1a military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0

**Mil-std (military Standard):**

Mil-c-5541 spec.