## NSN 5310-01-184-3786

Key Washer - Page 1 of 1

Mil-c-5541 spec.



View Online at https://aerobasegroup.com/nsn/5310-01-184-3786 **Hole Diameter:** Between 0.785 inches and 0.800 inches **Outside Diameter:** 1.200 inches **Tapered Key Minor Width:** 0.120 inches **Overall Distance Including Keys:** Between 1.470 inches and 1.570 inches **Material Thickness:** 0.063 inches Wire Hole Diameter: Between 0.070 inches and 0.075 inches **Special Features:** Distance from wire hole center to end of tapered key 0.060 in.; distance from wire hole center to top of tapered prebent key 0.120 in.; tapered key prebent 30 degrees min, 40 degrees max; hole width across flats 0.655 in. Min, 0.670 in. Max; distance from centerline to flatted bottom of washer 0.485 in. Min, 0.515 in. Max; distance from bottom of washer to inside of prebent key 1.160 in. Material: Aluminum alloy 2024 **Material Specification:** Qq-a-250/4, t4 federal specification single material response **Surface Treatment:** Chromate **Surface Treatment Specification:** Mil-c-5541, type 2, cl 1a military specification single treatment response Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig: A022b0 Mil-std (military Standard):