NSN 5310-01-187-3481



Plate Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-187-3481 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.280 inches nut Lubrication: Dry film lubricant **Overall Height:** 0.745 inches **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 0.967 inches **Nut Height:** 0.360 inches **Plate Thickness:** 0.020 inches Plate Width: Between 0.615 inches and 0.635 inches **Nut Counterbore Depth:** 0.125 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.371 inches and 0.381 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.750 inches and 0.754 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unjf **Features Provided:**

28

Floating nut

Thready Qty Per Inch (tpi):

NSN 5310-01-187-3481

Plate Self-locking Nut - Page 2 of 2



| Thread Size: |
|--------------------------------------------------------------------------------------------------------------------|
| 0.250 inches |
| Material: |
| Steel washer |
| Material Specification: |
| Ams 3304 assn standard 1st material response seal or mil-r-25988 military specification 2nd material response seal |
| Surface Treatment: |
| Passivate shell |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response washer |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A021a0 |
| Mil-std (military Standard): |
| Mil-r-25988 spec. |