

View Online at <https://aerobasegroup.com/nsn/5310-01-191-2480>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Head Style:**

Flat countersunk

**Head Diameter:**

0.529 inches

**Nut Style:**

Blind rivet w/smooth round shank

**Nut Diameter:**

Between 0.328 inches and 0.332 inches

**Nut Length:**

Between 1.314 inches and 1.344 inches

**Err Default:**

+0.421/+0.481 inches

**Shank End Type:**

Closed

**Thread Series:**

Unf

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Head Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Threads treated with rust inhibitor ferrocote 364, fscm 77490 per mil-c-16173, gr 3

**Material:**

Steel comp 4037 or steel comp 8740

**Material Specification:**

Mil-s-6049 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-s-6049 spec.