

View Online at <https://aerobasegroup.com/nsn/5310-01-193-9721>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.195 inches nut and 0.200 inches nut

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

1.375 inches

**Nut Height:**

0.483 inches

**Plate Thickness:**

Between 0.023 inches and 0.027 inches

**Plate Width:**

Between 0.830 inches and 0.850 inches

**Nut Counterbore Depth:**

0.338 inches nut and 0.348 inches nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.557 inches and 0.567 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 1.123 inches and 1.127 inches

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Special Features:**

Spring loaded; nut extends below base

**Material:**

Steel comp 8740 nut

**Material Specification:**

Aisi assn standard single material response nut or ams 6322 assn standard single material response nut

**Surface Treatment:**

Passivate shell

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0