## NSN 5310-01-193-9729

Lock Washer - Page 1 of 1



or

or

View Online at https://aerobasegroup.com/nsn/5310-01-193-9729

Hole Diameter:
Between 0.255 inches and 0.267 inches
Outside Diameter:
0.493 inches
Material Thickness:
0.062 inches
Hardness Rating:
Between 45.0 rockwell c and 53.0 rockwell c
Criticality Code Justification:
Zzzy
Special Features:
Rockwell c scale, hardness rating, 300 series material 35.0 min 43.0 max
Material:
Steel comp 420 or steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 o
steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or
steel comp 314 or steel comp 3140 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 3310h or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 3310h or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 3310h or steel comp 318l or
steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385
Material Specification:
66 federal standard all material responses
Special Test Features:
Special quality control testing
Style Designator:
Split helical-right hand
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
B class or c class and 2 style
Reference Number Differentiating Characteristics:
As differentiated by material which must conform to ships parts control center special quality control provisions and certified free from
mercury contamination
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A022b0