

View Online at <https://aerobasegroup.com/nsn/5310-01-196-8009>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.317 inches nut

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.130 inches and 0.135 inches

**Nut Style:**

Plate

**Nut Length:**

1.003 inches

**Nut Height:**

0.577 inches

**Plate Thickness:**

0.050 inches

**Plate Width:**

0.580 inches

**Nut Counterbore Depth:**

0.312 inches nut and 0.327 inches nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.354 inches and 0.364 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.716 inches and 0.720 inches

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.3125 inches

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5525 assn standard single material response or ams 5732 assn standard single material response or ams 5731 assn standard single material response

**Precious Material And Location:**

Threads silver

**Precious Material:**

Silver

**Surface Treatment:**

Passivate shell

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response threads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0