NSN 5310-01-198-8065

Blind Rivet Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-198-8065

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| 0.529 inches |
| Nut Style: |
| Blind rivet w/smooth round shank |
| Nut Diameter: |
| Between 0.328 inches and 0.332 inches |
| Nut Length: |
| Between 1.376 inches and 1.406 inches |
| Err Default: |
| +0.481/+0.541 inches |
| Shank End Type: |
| Closed |
| Thread Series: |
| Unf |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches |
| Head Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Special Features: |
| Threads coated with rust inhibitor ferrocote 364, fscm 77490 per mil-c-16173, gr 3 |
| Material: |
| Steel comp 4037 or steel comp 8740 |
| Material Specification: |
| Mil-s-6049 military specification single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Aaisi assn standard 1st treatment response or mil-s-6049 military specification 2nd treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5310-01-198-8065

Blind Rivet Plain Nut - Page 2 of 2



Fiig:

A021a0

Mil-std (military Standard):

Mil-s-6049 spec.