NSN 5310-01-202-9392

Round Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-202-9392

| Thread Class: |
|--|
| 2b |
| Thread Direction: |
| Right-hand |
| Flange Thickness: |
| Between 0.094 inches and 0.095 inches |
| Small End Diameter: |
| Between 0.290 inches and 0.294 inches |
| Drive Point Depth: |
| 0.060 inches |
| Nut Diameter: |
| Between 0.560 inches and 0.562 inches |
| Nut Thickness: |
| 0.331 inches |
| Drive Point Width: |
| 0.060 inches |
| Undercut Thickness: |
| 0.071 mils and 0.072 centimeters |
| Drive Point Quantity: |
| 2 |
| Thread Series: |
| Uns |
| Thready Qty Per Inch (tpi): |
| 80 |
| Thread Size: |
| 0.190 inches |
| Product Name: |
| Navy special project |
| Special Features: |
| Drive slots are in second end |
| Material: |
| Steel comp 303se |
| Material Specification: |
| Astm 582, cond a, cold finished assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Mil-f-14072, finish e300 military specification single treatment response or qq-p-35 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5310-01-202-9392

Round Plain Nut - Page 2 of 2



Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-f-14072 spec.