

NSN 5310-01-207-1710 Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-207-1710 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Height:** 0.040 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** 0.436 inches **Head Minor Diameter:** Between 0.370 inches and 0.374 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** 0.350 inches **Nut Length:** Between 0.827 inches and 0.857 inches **Nut Grip Range:** +0.220/+0.280 inches **Shank End Type:** Closed **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** 

Unjf

Thready Qty Per Inch (tpi):

**Thread Size:** 

0.250 inches

**Head Major Countersink Angle:** 

Between 75.75 degrees and 76.25 degrees

**Head Minor Countersink Angle:** 

Between 59.75 degrees and 60.25 degrees

Material:

Steel comp 304 or steel comp 305

**Material Specification:** 

Qq-s-763, cond 4 federal specification all material responses

## NSN 5310-01-207-1710

A021a0

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment:
Cadmium
Surface Treatment Specification:
$\ensuremath{Qq\text{-}p\text{-}416},$ type 2, class 2, federal specification all treatment responses
Specification Data:
80250-nas1735 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: