

View Online at https://aerobasegroup.com/nsn/5310-01-209-7231

| New Online at https://aerobasegroup.com/nsn// |
|---|
| Thread Class:                                 |
| 3b  |
| Thread Direction:                             |
| Right-hand                                    |
| Locking Feature:                              |
| Prevailing torque all metal design            |
| Counterbore Diameter:                         |
| 0.254 inches nut                              |
| Lubrication:                                  |
| Dry film lubricant                            |
| Overall Length:                               |
| 72.280 inches                                 |
| Overall Width:                                |
| 0.532 inches                                  |
| Nut Style:                                    |
| Gang channel, self locking                    |
| Removable Nut Manufacturer Code:              |
| 72962   |
| Channel Style:                                |
| Straight type                                 |
| Assemblyheight:                               |
| 0.482 inches                                  |
| Channel Height:                               |
| 0.298 inches                                  |
| Nut Spacing:                                  |
| 1.000 inches                                  |
| Nut Counterbore Depth:                        |
| 0.250 inches nut                              |
| Removable Nut Manufacturer Part Number:       |
| G11370-4-4                                    |
| Tempurature Rating:                           |
| 450.0 degrees fahrenheit                      |
| Nut Quantity:                                 |
| 72  |
| Thread Series:                                |
| Unjf  |
| Features Provided:                            |
| Floating nut                                  |
| Thready Qty Per Inch (tpi):                   |
| 28  |
| Thread Size:                                  |
| 0.050 inches                                  |

0.250 inches



Special Features:

Tensile strength 160 ksi nom.; dry film lubricant

#### Material:

Iron alloy 660 nut

### Surface Treatment:

Plastic channel

## Surface Treatment Specification:

Mil-c-27725, type 2, class b military specification single treatment response channel

Shelf Life:

N/a

#### Unit Of Measure:

---

# **Demilitarization:** No

Fiig:

A021a0

#### Mil-std (military Standard):

Mil-c-27725 spec.