
Plate Self-locking Nut - Page 1 of 2





Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.168 inches nut

Lubrication:

Soluble lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

0.692 inches

Nut Height:

0.250 inches

Plate Thickness:

0.047 inches

Plate Width:

Between 0.230 inches and 0.297 inches

Nut Counterbore Depth:

0.062 inches nut

Nut Mounting Provision:

Countersunk holes or dimpled holes

Mounting Provision Location:

Opposite nut projection side

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

0.234 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.466 inches and 0.470 inches

Tempurature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjc

Thready Qty Per Inch (tpi):

32

Hardness Rating:

49.0 rockwell c

NSN 5310-01-209-7248

Plate Self-locking Nut - Page 2 of 2



Thread Size:

0.164 inches

Mounting Hole Countersink Angle:

Between 98.0 degrees and 102.0 degrees

Special Features:

Dimpled hole diameter 0.098 in min, 0.113 in max

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0