## NSN 5310-01-209-9386

Gang Channel Self-locking Nut Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-209-9386 **Thread Class: Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design Lubrication: Dry film lubricant **Overall Length:** 71.575 inches **Overall Width:** 0.442 inches **Nut Style:** Gang channel, self locking **Removable Nut Manufacturer Code:** 72962 **Channel Style:** Straight type Assemblyheight: 0.437 inches **Channel Height:** 0.250 inches **Nut Spacing:** 1.125 inches **Removable Nut Manufacturer Part Number:** G11370-4-3 **Tempurature Rating:** 450.0 degrees fahrenheit **Nut Quantity:** 64 **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Special Features:** Tensile strength 160 ksi nom.; dry film lubricant

Material:

Iron alloy 660 nut

## NSN 5310-01-209-9386

Gang Channel Self-locking Nut Assembly - Page 2 of 2



	Trea		

Anodize channel and paint channel

## **Surface Treatment Specification:**

Mil-a-8625, type ii, class 1 military specification 1st treatment response mounting and mil-c-27725, type ii, class b, 2 coats military specification 2nd treatment response mounting

She	. 1.	. :	£
<b>UI10</b>	711	_	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.