

View Online at <https://aerobasegroup.com/nsn/5310-01-210-6258>

Thread Class:

2b

Thread Direction:

Right-hand

Counterbore Diameter:

2.125 inches first end and 2.135 inches first end

Small End Diameter:

Between 2.175 inches and 2.195 inches

Drive Point Depth:

Between 0.105 inches and 0.135 inches

Nut Style:

Round

Nut Diameter:

Between 2.490 inches and 2.510 inches

Nut Thickness:

Between 0.340 inches and 0.360 inches

Drive Point Width:

Between 0.180 inches and 0.200 inches

Undercut Thickness:

Between 0.110 inches and 0.130 inches

Drive Point Quantity:

4

Nut Counterbore Depth:

0.050 inches first end and 0.070 inches first end

Thread Series:

Un

Thready Qty Per Inch (tpi):

20

Hardness Rating:

Between 28.0 rockwell c and 34.0 rockwell c

Thread Size:

2.125 inches

Countersink Angle:

90.0 degrees second end

Bearing Surface Finish:

63.0 microinches

Material:

Steel comp 4130 or steel comp 4140 or steel comp 4340

Material Specification:

Astm a331 assn standard all material responses or ams 6414 assn standard 3rd material response or ams 6415 assn standard 3rd material response or astm a322 assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 1 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0