

View Online at <https://aerobasegroup.com/nsn/5310-01-212-0104>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design or prevailing torque with nonmetallic insert

Pilot Diameter:

Between 0.321 inches and 0.325 inches

Pilot Length:

Between 0.110 inches and 0.140 inches

Lubrication:

Dry film lubricant

Nut Style:

Spline

Nut Height:

Between 0.267 inches and 0.327 inches

Width Across Flats:

Between 0.423 inches and 0.453 inches

Tempurature Rating:

250.0 degrees fahrenheit

Thread Series:

Unf

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0