NSN 5310-01-216-4004

Lock Washer - Page 1 of 1

A022b0



View Online at https://aerobasegroup.com/nsn/5310-01-216-4004 **Hole Diameter:** Between 8.13 millimeters and 8.36 millimeters **Outside Diameter:** 14.96 millimeters **Material Thickness:** Between 1.98 millimeters and 2.24 millimeters Min. Tensile Strength (psi): 80000 pounds per square inch **Special Features:** Surface treatment per qq-p-35 Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316I or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 303 or steel comp 303se **Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-s-763 federal specification 7th material response or qq-s-763 federal specification 8th material response or gg-s-763 federal specification 9th material response or gg-s-763 federal specification 10th material response or astm a582 assn standard 11th material response or astm a582 assn standard 12th material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Style Designator:** Split helical-right hand Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: