

View Online at <https://aerobasegroup.com/nsn/5310-01-216-7894>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.195 inches base and 0.200 inches base

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

Between 1.360 inches and 1.390 inches

Nut Height:

0.403 inches

Plate Thickness:

Between 0.023 inches and 0.027 inches

Plate Width:

0.865 inches

Nut Counterbore Depth:

0.258 inches base and 0.268 inches base

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.557 inches and 0.567 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 1.123 inches and 1.127 inches

Thread Series:

Unjf

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Special Features:

Surface treatment must meet salt spray test requirements of qq-p-416, type 2; spring loaded boss extends below base

Material:

Steel comp 631 base

Surface Treatment:

Passivate clip

Surface Treatment Specification:

Qq-p-416, cl 2 federal specification 1st treatment response nut or qq-p-416, type 2 federal specification 2nd treatment response nut

Specification Data:

80205-nas1803 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0