## NSN 5310-01-216-8260

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-216-8260 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.195 inches nut and 0.200 inches nut Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 1.375 inches **Nut Height:** 0.373 inches **Plate Thickness:** Between 0.023 inches and 0.027 inches Plate Width: Between 0.830 inches and 0.850 inches **Nut Counterbore Depth:** 0.228 inches nut and 0.238 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center:** Between 0.557 inches and 0.567 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 1.123 inches and 1.127 inches **Thread Series:** Unjf **Features Provided:** Floating nut

Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Special Features:** Spring loaded; nut extends below base

## NSN 5310-01-216-8260

Plate Self-locking Nut - Page 2 of 2

A021a0



| material:  |
|--|
| Steel comp 8740 nut  |
| Material Specification:  |
| Aisi assn standard single material response nut or ams 6322 assn standard single material response nut |
| Surface Treatment:   |
| Passivate shell  |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 2 federal specification single treatment response nut                             |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Filg:  |