NSN 5310-01-220-5493

Thread Class:

3b

View Online at https://aerobasegroup.com/nsn/5310-01-220-5493

Double Hexagon Extended Washer Self-locking Nut - Page 1 of 2



| Thread Direction: | | | |
|---|--|--|--|
| Right-hand | | | |
| Washer Outside Diameter: | | | |
| 0.327 inches | | | |
| Lubrication: | | | |
| Dry film lubricant | | | |
| Overall Height: | | | |
| 0.193 inches | | | |
| Washer Thickness: | | | |
| 0.051 inches | | | |
| End Application: | | | |
| Tf-34 engine | | | |
| Width Across Flats: | | | |
| Between 0.243 inches and 0.251 inches | | | |
| Tempurature Rating: | | | |
| 1400.0 degrees fahrenheit | | | |
| Thread Series: | | | |
| Unjf | | | |
| Thready Qty Per Inch (tpi): | | | |
| 32 | | | |
| Thread Size: | | | |
| 0.190 inches | | | |
| Criticality Code Justification: | | | |
| Feat | | | |
| Special Features: | | | |
| Tiolube 660-1 coating | | | |
| Material: | | | |
| Nickel alloy uns n07001 | | | |
| Material Specification: | | | |
| Ams5709 assn standard single material response | | | |
| Precious Material: | | | |
| Silver | | | |
| Surface Treatment: | | | |
| Silver threads | | | |
| Surface Treatment Specification: | | | |
| F50tf70 class a mfr ref single treatment response | | | |
| Specification Data: | | | |
| 0748250tf19 manufacturers specification | | | |
| Shelf Life: | | | |
| N/a | | | |
| | | | |

NSN 5310-01-220-5493

Double Hexagon Extended Washer Self-locking Nut - Page 2 of 2



| | nit | O+ | Measure: |
|---|-----|----|-----------|
| u | | v | wicasuic. |

--

Demilitarization:

No

Fiig:

A021a0