

View Online at https://aerobasegroup.com/nsn/5310-01-228-9998

Bo Thread Direction: Righ-hand Locking Feature: Prevailing torque all metal design Washer Outside Diameter: 0.531 inches Lubrication: Soluble lubricant Overall Height: 0.280 inches Nut Style: Double hexagon Washer Thickness: 0.400 inches With Across Flats: Between 0.367 inches and 0.376 inches Thread Streics: Unjf Thread Streics: 0.31 inches Nut rated Nut rated Thread Streic: Unjf Thread Streic: Nut rated Thread Streic: Ox10 inches Material: Stel comp fol or steel comp h11 Material: Starla Creatment: Notel acadmium and chromate Starla Creatment: Notel acadmium and chromate	d Class:	
Tread Direction: Right-hand Right-hand Revailing Feature: Prevailing torque all metal design Macher Outside Diameter: 0.4351 Inches Lubrication: 0.531 Inches Lubrication: Soluble lubricant Overall Height: 0.420 Inches Not Style: Double hexagon Not Style: Double hexagon Not Style: Double hexagon Not Style: Double hoxagon Not Style: Style:		
Locking Feature: Prevailing torque all metal design Washer Outside Diametor: 0.531 inches Ubrication: Soluble lubricant Overall Height: 0.230 inches Overall Height: 0.230 inches Nut Style: Double hexagon Outole hexagon </td <td>d Direction:</td> <td></td>	d Direction:	
Locking Feature: Prevailing torque all metal design Washer Outside Diametor: 0.531 inches Ubrication: Soluble lubricant Overall Height: 0.230 inches Overall Height: 0.230 inches Nut Style: Double hexagon Outole hexagon </td <td>nand</td> <td></td>	nand	
Prevailing torque all metal design Washer Outside Diameter: 0.531 Inches Lubrication: Solubie Iubricant Overall Height: Outside Diameter: Overall Height: Outside Diameter: Ou		
Washer Outside Diameter: 0.531 inches 0.531 inches 0.531 inches Lubrication: Soluble lubricant Soluble lubricant 0.280 inches Outside Jubricant 0.280 inches Nut Style: 0.280 inches Double hexagon 0.40 inches Washer Thickness: 0.040 inches Width Across Flats: 0.440 inches Between 0.367 inches and 0.376 inches 0.440 inches Young Person 1.1 1.11111111111111111111111111111111111		
Lubrication: Soluble lubricant Overall Heigh: Soluble lubricant 0.280 linches Soluble labricant Nut Style: Soluble hexagon Duble hexagon Soluble hexagon Washer Thickness: Soluble hexagon 0.040 linches Soluble hexagon Width Across Flats: Soluble hexagon Between 0.367 linches and 0.376 linches Soluble hexagon Tompurature Rating: Soluble hexagon 90.01 degrees fahrenheit Soluble hexagon Unif Soluble hexagon Parkard Series: Soluble hexagon Unif Soluble hexagon Adreness Rating: Soluble hexagon Not rated Soluble hexagon Thread Size: Soluble hexagon 0.312 linches Soluble hexagon Stel comp 601 or stel comp h11 Soluble hexagon Material Size/ Soluble hexagon Starder Treatment: Soluble hexagon standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 648		
Soluble lubricant Overall Height: 0.280 inches Nut Style: Double hexagon Washer Thickness: 0.040 inches Width Across Flats: Between 0.367 inches and 0.376 inches Tempurature Rating: 00.0 degrees fahrenheit Thread Series: Unjf Thread State: Not rated Thread Size: 0.312 inches Material Exection: Naterial Exection: Material: Stel comp 601 or stel comp h11 Material Tesponse Material Tesponse Toread States States standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Strates Tesponse Strates Testensen: Notace Treatment:	inches	
Overall Height: 0.280 inches Nut Style: Double hexagon Washer Thickness: 0.400 inches With Across Flats: Between 0.367 inches and 0.376 inches Tempurature Rating: 900.0 degrees fahrenheit Thread Series: Unjf Thread Series: 0.312 inches 0.312 inches Matrial: 0.312 inches Matrial: Stel comp 601 or stel comp h11 Material: Matrial: Matrial: Matrial: Material: Materia: Materi	ation:	
0.280 indes Nut Style: Double hexagon Washer Thickness: 0.40 inches Width Across Flats: Between 0.367 inches and 0.376 inches Tempurature Rating: 900.0 degrees fahrenheit Thread Series: Unjf Thread Series: 0.312 inches Addition (tpi): 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd mater	e lubricant	
0.280 indes Nut Style: Double hexagon Washer Thickness: 0.040 inches Width Across Flats: Between 0.367 inches and 0.376 inches Tempurature Rating: 900.0 degrees fahrenheit Thread Series: Unjf Thread Series: 0.14 Across Rating: Not rated Thread Size: 0.312 inches Material: Stel comp 601 or stel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd materi	II Height:	
Double hexagon Washer Thickness: 0.040 inches Width Across Flats: Between 0.367 inches and 0.376 inches Tempurature Rating: 900.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Arse 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material compone or ams 6487 as	inches	
Washer Thickness: 0.040 inches 0.040 inches Width Across Flats: Between 0.367 inches and 0.376 inches Tempurature Rating: 00.0 degrees fahrenheit Thomad Series: 101/1 Thread Series: Unif Thread Yap Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Amerial Size: Not steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Material Specification: X Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11	yle:	
Washer Thickness: 0.040 inches 0.040 inches Width Across Flats: Between 0.367 inches and 0.376 inches Tempurature Rating: 00.0 degrees fahrenheit Thomad Series: 101/1 Thread Series: Unif Thread Yap Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Amerial Size: Not steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Material Specification: X Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11 Material Size: Steel comp 601 or steel comp h11		
Width Across Flats: Between 0.367 inches and 0.376 inches Tempurature Rating: 900.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd mate		
Between 0.367 inches and 0.376 inches Tempurature Rating: 900.0 degrees fahrenheit Thread Series: Unjf Thread Yup Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	inches	
Tempurature Rating: 900.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	Across Flats:	
900.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	en 0.367 inches and 0.376 inches	
Thread Series: Unjf Thready Qty Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	urature Rating:	
Unif Thready Qty Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	degrees fahrenheit	
Thready Qty Per Inch (tpi): 24 Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard	d Series:	
24 Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 6485 assn standard 2nd material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material respons		
Hardness Rating: Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 64	dy Qty Per Inch (tpi):	
Not rated Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate		
Thread Size: 0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	ess Rating:	
0.312 inches Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	red	
Material: Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	d Size:	
Steel comp 601 or steel comp h11 Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	inches	
Material Specification: Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	al:	
Ams 6304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd material response Surface Treatment: Nickel and cadmium and chromate	comp 601 or steel comp h11	
response Surface Treatment: Nickel and cadmium and chromate	al Specification:	
Surface Treatment: Nickel and cadmium and chromate	304 assn standard 1st material response or ams 6485 assn standard 2nd material response or ams 6487 assn standard 2nd i	nateria
Nickel and cadmium and chromate	ise	
	e Treatment:	
Surface Treatment Specification:	and cadmium and chromate	
	e Treatment Specification:	
Ams 2416 assn standard single treatment response	416 assn standard single treatment response	
Shelf Life:	Life:	
N/a		
Unit Of Measure:	f Measure:	

No

NSN 5310-01-228-9998 Double Hexagon Extended Washer Self-locking Nut - Page 2 of 2

AeroBase Group

Fiig: A021a0