## NSN 5310-01-230-0405

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-230-0405 **Thread Class:** 2b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with metallic insert **Counterbore Diameter:** 0.196 inches and 0.202 inches **Mounting Hole Diameter:** Between 0.128 inches and 0.135 inches **Nut Style:** Plate **Nut Length:** Between 0.975 inches and 0.995 inches **Nut Height:** Between 1.580 inches and 1.620 inches **Plate Thickness:** Between 0.050 inches and 0.070 inches Plate Width: Between 0.386 inches and 0.406 inches **Nut Counterbore Depth:** 1.170 inches and 1.190 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** 0.344 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.686 inches and 0.690 inches **Thread Series:** Unf Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches Material:

Aluminum alloy 6061 **Material Specification:** Mil-a-12545 military specification single material response **Surface Treatment:** Anodize

## NSN 5310-01-230-0405

Plate Self-locking Nut - Page 2 of 2



| Surface Treatment Sp | pecification: |
|----------------------|---------------|
|----------------------|---------------|

Mil-a-8625, type 1 military specification single treatment response

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-12545 spec.