

View Online at <https://aerobasegroup.com/nsn/5310-01-232-9772>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.460 inches nut

Lubrication:

Dry film lubricant

Overall Height:

1.140 inches

Mounting Hole Diameter:

Between 0.130 inches and 0.135 inches

Nut Style:

Plate

Nut Length:

1.550 inches

Nut Height:

0.600 inches

Plate Thickness:

0.020 inches

Plate Width:

1.070 inches

Nut Counterbore Depth:

0.090 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.620 inches and 0.630 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 1.248 inches and 1.252 inches

Temperature Rating:

250.0 degrees fahrenheit

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

20

Hardness Rating:

46.0 rockwell c

Thread Size:

0.438 inches

Material:

Steel comp 4130 or steel comp 1031 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541 or steel comp 1042 or steel comp 1043 or steel comp 1044 or steel comp 1045 or steel comp 1548 or steel comp 1049 or steel comp 1551 or steel comp 1552 or steel comp 1053 or steel comp 1055 or steel comp 1059 or steel comp 1060 or steel comp 1561 or steel comp 1064 or steel comp 1065 or steel comp 1566 or steel comp 1069 or steel comp 1572 or steel comp 1030

Material Specification:

Mil-s-18729 military specification 1st material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-r-6855 spec.