Blind Rivet Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-239-5918

| Thread Class: |
|---|
| 3b |
| Thread Direction: |
| Right-hand |
| - |
| Head Style: |
| Eliptical countersunk |
| Head Height: 0.040 inches |
| |
| Locking Feature: |
| Prevailing torque all metal design |
| Head Major Diameter: |
| Between 0.4176 inches and 0.4400 inches |
| Head Minor Diameter: |
| 0.3500 inches |
| Lubrication: |
| Dry film lubricant |
| Nut Style: |
| Blind rivet w/smooth round shank |
| Nut Diameter: |
| Between 0.325 inches and 0.327 inches |
| Nut Length: |
| Between 0.507 inches and 0.537 inches |
| Nut Grip Range: |
| +0.060/+0.080 inches |
| Shank End Type: |
| Open |
| Tempurature Rating: |
| 450.0 degrees fahrenheit |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.2500 inches |
| Head Major Countersink Angle: |
| Between 75.0 degrees and 77.0 degrees |
| Head Minor Countersink Angle: |
| Between 59.0 degrees and 61.0 degrees |
| Material: |
| Steel comp 304 or steel comp 305 |
| Material Specification: |
| Qq-s-763, cond a federal specification single material response |
| |

NSN 5310-01-239-5918

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Specification Data:

80205-nas1734 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0