

View Online at <https://aerobasegroup.com/nsn/5310-01-241-2680>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.062 inches nut

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

0.953 inches

Nut Height:

0.415 inches

Plate Thickness:

0.030 inches

Plate Width:

0.410 inches

Nut Counterbore Depth:

0.194 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.339 inches and 0.349 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.686 inches and 0.690 inches

Temperature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Product Name:

Navy special project

Material:

Steel comp 1030 or steel comp 1033 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1042 or steel comp 1043 or steel comp 1045 or steel comp 1046 or steel comp 1049 or steel comp 1050 or steel comp 1055 or steel comp 1060 or steel comp 1064 or steel comp 1065 or steel comp 1566 or steel comp 1070

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0