NSN 5310-01-243-9425

Plate Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-243-9425

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Lubrication: |
| Soluble lubricant |
| Mounting Hole Diameter: |
| Between 0.130 inches and 0.135 inches |
| Nut Style: |
| Plate |
| Nut Length: |
| 1.050 inches |
| Nut Height: |
| 0.775 inches |
| Plate Thickness: |
| 0.025 inches |
| Nut Mounting Provision: |
| Straight holes |
| Mounting Hole Arrangement Style: |
| 2 holes |
| Distance From Aperture Center To Mounting Hole Center: |
| Between 0.495 inches and 0.505 inches |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5525 assn standard single material response or ams5737 assn standard single material response |
| Precious Material And Location: |
| Barrel and stud silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Passivate seal |
| Surface Treatment Specification: |
| Mil-s-5002 military specification single treatment response seal |
| Shelf Life: |

N/a

NSN 5310-01-243-9425

Plate Plain Nut - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-5002 spec.