

View Online at <https://aerobasegroup.com/nsn/5310-01-244-2258>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.220 inches nut

**Lubrication:**

Dry film lubricant

**Overall Height:**

0.405 inches

**Mounting Hole Diameter:**

0.098 inches

**Nut Style:**

Plate

**Nut Length:**

0.840 inches

**Nut Height:**

0.268 inches

**Plate Thickness:**

0.030 inches

**Plate Width:**

0.443 inches

**Nut Counterbore Depth:**

0.070 inches nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.290 inches and 0.300 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.588 inches and 0.592 inches

**Temperature Rating:**

Between 65.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

60.0 shore durometer a

**Thread Size:**

0.190 inches

**Material:**

Rubber butadiene-acrylonitrile class nbr seal

**Material Specification:**

Mil-r-6855, class 1, grade 60 military specification single material response seal

**Surface Treatment:**

Passivate washer

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response washer

**Specification Data:**

80205-nas1774 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-r-6855 spec.