

View Online at <https://aerobasegroup.com/nsn/5310-01-246-5966>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.352 inches nut

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.130 inches and 0.135 inches

**Nut Style:**

Plate

**Nut Length:**

1.290 inches

**Nut Height:**

0.790 inches

**Plate Thickness:**

0.020 inches

**Plate Width:**

0.762 inches

**Nut Counterbore Depth:**

0.410 inches nut

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.495 inches and 0.505 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.998 inches and 1.002 inches

**Temperature Rating:**

Between 65.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Thread Series:**

Unj

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.3125 inches

**Material:**

Stainless steel washer

**Material Specification:**

Mil-r-6855 class 1, gr 60 military specification single material response except threads

**Surface Treatment:**

Passivate nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-r-6855 spec.