Hexagon Self-locking Nut - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5310-01-274-5665

| Thread Class: | |
|------------------------|---|
| 3b | |
| Thread Direction: | |
| Right-hand | |
| Nut Style: | |
| Hexagon | |
| Nut Height: | |
| Between 0.575 inch | es and 0.610 inches |
| Width Across Flats | |
| Between 0.741 inch | es and 0.755 inches |
| Tempurature Ratin | g: |
| 250.0 degrees fahre | nheit |
| Thread Series: | |
| Unf | |
| Thready Qty Per In | ch (tpi): |
| 20 | |
| Thread Size: | |
| 0.500 inches | |
| Criticality Code Ju | stification: |
| Zzzw | |
| Bearing Surface Ty | /pe: |
| Chamfered or washe | er faced |
| Material: | |
| Nickel alloy and cop | oper alloy |
| Specification Data: | |
| 81349-mil-i-45208 g | overnment specification and 96906-mil-std-105 government standard and 96906-ms17828 government standard and |
| 81349-mil-n-24106 (| government specification and 96906-mil-std-129 government standard and 81349-mil-p-23199 government specificatior |
| and 96906-mil-std-2 | 132 government standard and 96906-mil-std-767 government standard |
| Departure From Cit | ted Document: |
| Material will be in ac | cordance with ships parts control center activity hx quality control, manufacturing and testing specifications |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A021a0 | |
| Mil-std (military Sta | andard): |
| Mil-i-45208 spec. | |